



Bitumen Primer



Versatile bituminous primer

Bitumen Primer is a locally manufactured bitumen solution suitable for sealing and priming porous and non-porous surfaces.

Fields of application

Bitumen Primer is a bitumen based primer for the surface conditioning of concrete and timber substrates prior to the application of heat fused APP and SBS modified bitumen membranes such as UniTorch.

Features

- Versatile bituminous primer for porous and non-porous surfaces
- Used on concrete, metal and timber surfaces
- Economical & easy to apply

Application

Bitumen Primer may be applied by brush or roller. The applied film must be allowed to dry before being overlaid with any waterproofing treatment so as to avoid solvent entrapment.

Physical Properties - application

Volume solids	40%
Ovecoating time at 25°C	Min 24 hours
Drying time at 25°C	± 4 hours

Surface preparation

As with all surface coatings, good preparation is of paramount importance to the success and long-life of the system.

- Ensure that the surface to be treated is dry and sound, free of loose, dusting or flaking particles and free from contaminants such as grease and fungus.
- Defects such as cracks, broken mortar joints, etc. are to be repaired prior to primer application.

Physical Properties - wet material

Density	0,90 g/cm ²
Colour	Black
Flash point	30°C
Dilution	White spirits or turps
Consistency	Low viscosity liquid

Specifications are subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

Precautions

- Do not apply if temperature is below 5°C.
- Product is not resistant to solvents when dry.
- Bitumen Primer contains a flammable solvent, all normal precautions against fire should be taken during storage and use.
- Keep away from sources of ignition.

Safety

- Flammable
- Solvent based product - toxic
- Ensure adequate ventilation
- Do not smoke or use flame during application
- If Bitumen Primer comes into contact with eyes, rinse with plenty of clean water and seek medical attention

Storage

- Store in original containers in a cool, dry place.
- Maximum shelf life – 24 months (under normal conditions).



Manufactured in SA for SA conditions

Version 001-201203

Disclaimer: The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subject to change without prior notice.

Available from Waterproofing Centres countrywide

www.waterproofingcentre.co.za

Cape Town

Tel 021 448 7880
Fax 021 448 7897

Gauteng

Tel 011 608 0317
Fax 011 608 0347

KwaZulu-Natal

Tel 031 569 3963
Fax 031 569 1849

Port Elizabeth

Tel 041 365 2936
Fax 041 365 6475

East London

Tel 043 722 5676
Fax 043 722 5676

Brackenfell

Tel 021 981 8343

George

Tel 044 874 3905
Fax 044 874 3907

Margate

Tel 039 312 2764
Fax 039 312 2673

Nelspruit

Tel 013 752 4409
Fax 013 752 6556

email

assist@
waterproofingcentre.co.za