



Davco Primer



Primer, sealer and bonding agent

Davco Primer is used as a primer, sealer and bonding agent to prepare floor surfaces prior to the application of the waterproofing membrane and wall coating system.

Fields of application

- Reduce dust and increase bonding of the substrate
- Act as a bonding agent to old floors
- Prime and use as a bonding agent on smooth concrete finishes
- Seal pores on rough porous concrete to eliminate air bubbles
- As a primer on bitumen membrane prior to the application of Sovacryl

Technical data

| | |
|------------------|---------------------------------|
| Specific gravity | 1,01 |
| Flash point | Non flammable |
| Drying time | 30 minutes |
| Water resistance | Very good |
| Coverage | 8 - 10 m ² per litre |

Specifications are subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

Surface preparation

- Ensure that the surface is dry, clean and free from curing compound or release agents.
- No chipping or roughening of surface is required if the condition is stable. Old paint work which is stable can remain.
- Any contamination, including commercial detergents used for cleaning, must be thoroughly rinsed off with plenty of water.

Application

Apply Davco Primer to clean floor with roller, brush and squeegee. Allow to dry until a clear film appears. The primer is dry when all milkyiness disappears.

Packaging

Davco Primer is available in 5 litre and 20 litre containers.

Shelf life

Shelf life of up to 12 months from the date of manufacture. Store in a cool place away from direct sunlight. Avoid freezing of the primer.

Health and safety

Davco Primer is non toxic. In case of excessive skin contact, thoroughly flush with clean water. If ill effects occur, seek medical attention promptly.

Version 001-201203

Disclaimer: The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subject to change without prior notice.

Available from Waterproofing Centres countrywide

www.waterproofingcentre.co.za

Cape Town

Tel 021 448 7880
Fax 021 448 7897

Gauteng

Tel 011 608 0317
Fax 011 608 0347

KwaZulu-Natal

Tel 031 569 3963
Fax 031 569 1849

Port Elizabeth

Tel 041 365 2936
Fax 041 365 6475

East London

Tel 043 722 5676
Fax 043 722 5676

Brackenfell

Tel 021 981 8343

George

Tel 044 874 3905
Fax 044 874 3907

Margate

Tel 039 312 2764
Fax 039 312 2673

Nelspruit

Tel 013 752 4409
Fax 013 752 6556

email

assist@
waterproofingcentre.co.za