



neoprene primer

Bonding Primer

Neoprene Primer has been specifically designed to improve the adhesion of self adhesive waterproofing membranes to concrete, masonry, timber and metal surfaces.

Uses

As a bonding primer for:

- Uniflash bandage flashings
- Sylbond FB 150
- DB 300 self adhesive membrane
- DB 350 self adhesive membrane
- Tilesafe self adhesive membrane

Features

Neoprene Primer has excellent brushing characteristics and is flexible and elastic to allow for slight substrate movement.

Application

All surfaces must be clean, dry and dust free.

Apply by means of a brush or roller.

Self adhesive membranes may be applied to the Neoprene primed surface within 15 minutes of the primer application.

Technical Data

Heat Resistance	Up to 100°C
Coverage	3 to 4 m ² per litre (per coat)
Colour	Light grey
Consistency	Thin liquid
Base	Synthetic neoprene rubber

Packaging

Neoprene Primer is available in tins of 1ℓ, 5ℓ and 25ℓ.



Shelf Life

Shelf life of up to 12 months in original, unopened containers although thickening may occur (from the date of manufacture). Store in a cool place away from direct sunlight.

Precautions

! Highly flammable when wet.

Do not smoke or use naked flame in the vicinity of application.

- Do not use in confined spaces.
- Store away from heat.
- Do not apply during cold, inclement weather as surface condensation may impair the bond strength of the primer.
- Protect from freezing during storage.

Version 001-201307



Manufactured in SA, for SA conditions

Disclaimer: The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subject to change without prior notice.

Available from Waterproofing Centres countrywide

www.waterproofingcentre.co.za

Cape Town

Tel 021 448 7880
Fax 021 448 7897

Gauteng

Tel 011 608 0317
Fax 011 608 0347

KwaZulu-Natal

Tel 031 569 3963
Fax 031 569 1849

Port Elizabeth

Tel 041 365 2936
Fax 041 365 6475

East London

Tel 043 722 5676
Fax 043 722 5676

Brackenfell

Tel 021 981 8343

George

Tel 044 874 3905
Fax 044 874 3907

Margate

Tel 039 312 2764
Fax 039 312 2673

Nelspruit

Tel 013 752 4409
Fax 013 752 6556

email

assist@
waterproofingcentre.co.za