



Sylbond TS200



Reinforced Self-Adhesive Waterproofing Membrane

Cold applied Sylbond TS200 waterproofing membrane comprises of a reinforced adhesive compound laminated to a mesh and is proudly *manufactured locally*.

Uses

- Provides instant waterproofing / tiling of balconies and areas to be tiled.
- Recommended as a tiling substrate (ie. tile directly onto the mesh with recommended tile adhesive)
- Facilitates immediate tiling after membrane is laid (no lost time).

Features

- The mesh is off-set during manufacturing.
- This creates a seldge of pure polymer bitumen adhesive on one side of the sheet.
- Will amalgamate, by a process of cold fusion, with the underside of the adjacent overlapping sheet.

Application

Tiles are applied using a conventional tile adhesive which initially keys to the mesh. As the tile adhesive dries, it forms a strong permanent bond through the mesh directly onto the waterproofing layer.

Technical data

Properties	Test Method	Metric
Adhesion – to primed steel	ASTM D1000	2,5 N/mm
Adhesion – to self	ASTM D1000	2,5 N/mm
Resistance to Acids, Alkalis & Salts		Excellent
Temperature range – application		10°C to 35°C
Temperature range – service		5°C to 70°C
Thickness – total	ASTM D1000	2 mm
Weight		2 kg / m ²
Recommended Primer		Primer D

Specifications are subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

Standard sizes

Roll width	Roll length	Coverage per roll
1 m	15 m	14 m ²

Safety

- Wash hands thoroughly with soap and water or a proprietary hand-cleaner prior to eating or smoking
- Launder contaminated clothing, gloves, etc

Storage

- Store upright in original containers in a cool, dry place
- Maximum shelf life – 6 months

version 001-201404

Disclaimer: The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subject to change without prior notice.



Available from Waterproofing Centres countrywide

www.waterproofingcentre.co.za

Cape Town

Tel 021 448 7880
Fax 021 448 7897

Gauteng

Tel 011 608 0317
Fax 011 608 0347

KwaZulu-Natal

Tel 031 569 3963
Fax 031 569 1849

Port Elizabeth

Tel 041 365 2936
Fax 041 365 6475

East London

Tel 043 722 5676
Fax 043 722 5676

Brackenfell

Tel 021 981 8343

George

Tel 044 874 3905
Fax 044 874 3907

Margate

Tel 039 312 2764
Fax 039 312 2673

Nelspruit

Tel 013 752 4409
Fax 013 752 6556

email

assist@
waterproofingcentre.co.za