



Uniflash



Fabric backed waterproofing membrane

Uniflash is a flexible, self-adhesive, elastomeric membrane. This product is ideally suited for quick and effective waterproofing of concrete and timber decks with good UV protection. This product is locally manufactured to suit our unique climate. Can also be used for the protection of steel against corrosion. The membrane consists of an inert polyester fabric laminated to a pressure sensitive, reinforced, modified bitumen adhesive.

Features

- Fast and easy application
- No heating or drying
- Conformable
- Compatible with common water based coatings

Standard sizes

Tape Width	Roll Length
100mm	15m
150mm	15m
200mm	15m
225mm	15m

Tape Width	Roll Length
250mm	15m
300mm	15m
450mm	15m
600mm	15m

Uses

A general waterproofing membrane for exposed applications including flashings for parapets.

Fields of Application

The **Uniflash** range has been designed and developed for waterproofing in situations such as:

- Counter flashing
- Ridge capping
- Pipe dressings
- Gutter sealing
- Flat roof repairs
- Valley linings
- Roof sheet laps
- Covering drive screws
- Counter flashing for torch applied membranes

continued overleaf...



Manufactured in SA for SA conditions

version 001-201203

Disclaimer: The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subject to change without prior notice.

Available from Waterproofing Centres countrywide

www.waterproofingcentre.co.za

Cape Town

Tel 021 448 7880
Fax 021 448 7897

Gauteng

Tel 011 608 0317
Fax 011 608 0347

KwaZulu-Natal

Tel 031 569 3963
Fax 031 569 1849

Port Elizabeth

Tel 041 365 2936
Fax 041 365 6475

East London

Tel 043 722 5676
Fax 043 722 5676

Brackenfell

Tel 021 981 8343

George

Tel 044 874 3905
Fax 044 874 3907

Margate

Tel 039 312 2764
Fax 039 312 2673

Nelspruit

Tel 013 752 4409
Fax 013 752 6556

email

assist@
waterproofingcentre.co.za



Technical data

Properties	Test Method	Metric
Adhesion – to primed steel	ASTM D1000	2,5 N/mm
Adhesion – to self	ASTM D1000	2,5 N/mm
Resistance to Acids, Alkalis & Salts		Excellent
Temperature range – application		10°C to 35°C
Temperature range – service		5°C to 70°C
Thickness – backing	ASTM D1000	300 µm
Thickness – adhesive	ASTM D1000	1200 µm
Thickness – total	ASTM D1000	1500 µm
Weight		1,5 kg/m ²
Recommended Primer		Primer D

Specifications are subject to change without notification. Results shown are typical but reflect test procedures used. Actual field performance will depend on installation methods and site conditions.

Surface Preparation

As with all surface coatings, thorough preparation is of paramount importance to the success and long-life of the system. Ensure that the surface to be treated is dry and sound, free of loose, dusting or flaking particles and free from contaminants such as grease and fungus.

Application

Uniflash is pressure bonded to prepared surfaces, which have been pre-primed with **Primer D**.

After the **Uniflash** waterproofing membrane has been applied a final topcoat application of **Geoflex Liquid Plastic** is to be applied by brush or roller.

Alternatively, acrylic exterior quality paint can be applied in a colour of your choice.

Safety

- Normal hygiene procedures
- Wash hands thoroughly with soap and water or a proprietary hand-cleaner prior to eating or smoking.
- Launder contaminated clothing, gloves, etc

Storage

- Store in original containers in a cool, dry place
- Maximum shelf life – 6 months



Manufactured in SA
for SA conditions

version 001-201203

Disclaimer: The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subject to change without prior notice.

Available from Waterproofing Centres countrywide

www.waterproofingcentre.co.za

Cape Town

Tel 021 448 7880
Fax 021 448 7897

Gauteng

Tel 011 608 0317
Fax 011 608 0347

KwaZulu-Natal

Tel 031 569 3963
Fax 031 569 1849

Port Elizabeth

Tel 041 365 2936
Fax 041 365 6475

East London

Tel 043 722 5676
Fax 043 722 5676

Brackenfell

Tel 021 981 8343

George

Tel 044 874 3905
Fax 044 874 3907

Margate

Tel 039 312 2764
Fax 039 312 2673

Nelspruit

Tel 013 752 4409
Fax 013 752 6556

email

assist@
waterproofingcentre.co.za