



## bitumen flashing

## Bitumen Mastic Sealant

*Bitumen Flashing compound is cut-back bitumen mastic, reinforced with inert fillers and plasticisers that air-dries to form a flexible watertight sealant.*

### Uses

Bitumen Flashing is designed to be used in conjunction with Fibremesh glass felt as a flashing system to almost any area requiring protection from the elements.

For use as a flashing compound on:

- Bituminous roof sheeting
- Cement and concrete
- Brickwork
- Wood
- Metal and galvanized sheets

### Features

It is durable and flexible and can be overcoated with most acrylic paints.

- Good adhesion to a variety of substrates
- Non-slumping
- Non-toxic, suitable for drinking water installations

### Application

Surfaces should be clean and dry.  
Apply undiluted by means of brush.  
When used in conjunction with Fibremesh, always place the reinforcement 'mesh to substrate'.

### Technical Data

Coverage	1.5 to 2m <sup>2</sup> per liter (per coat)
Application temp	10°C to 50°C
Drying Time	Surface dry: 4 to 6 hours Full cure: 14 days
Colour	Black
Consistency	Thin paste, non slumping



### Packaging

Bitumen Flashing is available in tins of 5ℓ and 25ℓ.

### Shelf Life

Shelf life of up to 6 months in unopened containers from the date of manufacture. Store in a cool place away from direct sunlight.

### Precautions

#### Flammable.

- Protect from naked flame during application.
- Product is prone to thickening on storage.
- Not resistant to solvent, fuels and lubricants.
- Not to be over coated with aluminium paint.



Manufactured in SA, for SA conditions

Version 001-201307

Disclaimer: The use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specifications are subject to change without prior notice.

Available from Waterproofing Centres countrywide

[www.waterproofingcentre.co.za](http://www.waterproofingcentre.co.za)

#### Cape Town

Tel 021 448 7880  
Fax 021 448 7897

#### Gauteng

Tel 011 608 0317  
Fax 011 608 0347

#### KwaZulu-Natal

Tel 031 569 3963  
Fax 031 569 1849

#### Port Elizabeth

Tel 041 365 2936  
Fax 041 365 6475

#### East London

Tel 043 722 5676  
Fax 043 722 5676

#### Brackenfell

Tel 021 981 8343

#### George

Tel 044 874 3905  
Fax 044 874 3907

#### Margate

Tel 039 312 2764  
Fax 039 312 2673

#### Nelspruit

Tel 013 752 4409  
Fax 013 752 6556

#### email

assist@  
waterproofingcentre.co.za